

PRO-CUT USA PFM 9.2 // BID SPEC SHEET



Pro-Cut's PFM lathes are the first choice of the brake service industry. They have been approved by virtually every auto manufacturer and are essential equipment for GM, Ford, and Nissan dealers in North America.

PFM 9.2 // FEATURES

The PFM 9.2 lathe provides smooth, non-directional finish in a single pass, removing up to 0.040" per cut. On-car function eliminates time-consuming removal of pressed-on or tapped rotors. Powerful motor turns 4x4 hubs easiiily. Cast aluminum body provides natural dampening and is virtually indestructible. Extra wide adjsutment range handles over-sized rotors with no problem. Rigid tool arm ensures that rotor surfaces will be parallel and perpendicular to spindle axis. SImple, easy-to-use adapters mount quickly. Automatice shutoff feature allows hands-free operation. New features include an improved trolley with dual bearings for friction-free movement and a disc brake for secure locking; also a speed-lock cutting head that can be placed and set with one hand.



PFM 9.2 // FUNCTION

The PFM 9.2 DRO lathe mounts on the vehicle hub and resurfaces the brake rotor. The machine's patented Rotor Matching System eliminates run-out in the rotor, effectively matching the rotor to the hub. The elimination of run-out in the rotor eliminates brake shudder or pulsation extending the life of rotors and pads. The fully patented PFM adjustment system is the only fully automatic compensation system on the market and requires no input from the tech.

PERFORMANCE SPECS	USA	Foreign	FEATURE CHECKLIST	5 Adapter pkg.	7 Adapter pkg.	MANUFACTURED BY:
Maximum Rotor Thickness Minimum Rotor Thickness Maximum Rotor Diameter Minimum Rotor Diameter Maximum Depth of Cut	1.75" 0.2" 17.2" 4.0" 0.020"/side	44mm 5 mm 437 mm 102 mm 0.38 mm	Brake Lathe Cutting tips (box of 10) Trolley Silencer Nut & Bolt Kit		© © ©	PRO-CUT USA 10 TECHNOLOGY DRIVE WEST LEBANON, NH 03784 P » 603-298-5200 F » 603-298-8404
Spindle Speed Carriage Speed	123 rpm 0.005"/rev	123 rpm 0.12 mm/rev	All Accessories 50-687 4 lug car adapter	& &	⊗ ⊗	INFO@PROCUTUSA.COM WWW.PROCUTUSA.COM
Motor Weight	1.0 hp 78 lbs	0.75 kW 35 kgs	50-688 5 lug car adapter 50-691 SUV/PU adapter	& &	& &	
Shipping Weight Electrical Supply	85 lbs 110v/1ph/60hz	85 kgs 230v/1ph/50hz	50-695 Lt PU adapter 50-694 Ford adapter 50-683 HD PU adapter	& &	⊗ ⊗ ⊗	ESSENTIAL EQUIPMENT
			50-935 Dual PU adapter		\otimes	UEW RECOMMEND

REV:01232012

PG» ØØ1