

NEVER OUTMATCHED



BASE LATHE UNIT / Cross-Platform Compatibility A10 WARTHOG W/ 8ADP SHOWN

Pro-Cut's A10 WARTHOG utilizes a rugged body casting design which is not only more rigid and stable, but has a heavy duty PTO drive system that provides nearly twice the start up torque of our other machines. A larger spindle, increased bearing separation, and thicker draw bar combine to give smoother cuts on larger vehicles. This lathe is ready to provide reliable service on any vehicle up through many medium duty trucks. A great machine for fleets, municipalities, truck shops, or high volume full line dealers.

WITH PRO-CUT. YOU CAN...

FIT ON EVERY VEHICLE We have the adapters that will connect you to virtually any vehicle on the road today and the power to turn stiff all-wheel drive and truck axles. And our simple set-up is the same from sub compact to heavy duty pick-up truck!

TRY BEFORE YOU BUY Before you invest in *Pro-Cut* you need to see it work in your shop with your techs. Save your toughest brake job and call us in and we'll show you and your staff how to make money with our lathes.

SERVICE ANY VEHICLE ON ANY LIFT IN 7-9 MINUTES. Two post, four post, drive-on... it doesn't matter. Pro-Cut's new fixed post trolley allows you to roll up and mount your Pro-Cut lathe with confidence.

FREE ON-SITE DEMO. GIVE US A CALL. Still not convinced? Call 1-800-543-6618 to set up a free on-site demo! Get hands on with the Pro-Cut Rotor Matching System with no obligations.

www.PROCUTUSA.com

SS-A10



A10 WARTHOG / TECH SPECS



STANDARD FEATURES

BENEFIT

Patented one touch Lateral Run Out (LRO) compensation
DRO "Live" digital computer display
Custom Calibrated Rate Sensor
One Piece Adapters for 3 lug Smart Car up to F750
Cross Platform Compatible Computer & wiring harness
Speed-Lock Cutting Head ·····
4 Wheel Fixed Column Custom trolley

Press one button and the latest PFM lathes compensate in less than 30 seconds! Displays actual live LRO of machine & tracks # of compensations and duration. Locks lathe in at .001" or less LRO every time you compensate for factory perfect cuts. For long hard shop use and compatible with older lathes.

Allows use of plug & play G2X measuring Cutting Head & full GYR Technology Package. Slides on dual dove-tail ways and a simple lever eliminates need for any set-up tools. Working Range of 21"to 43" allows the use on any lift or no lift!

A10 WARTHOG SPECIFICATIONS

SPEED LOCK CUTTING HEAD (Standard)

Maximum Rotor Thickness	1.75"
Minimum Rotor Thickness	0.20"
Maximum Rotor Diameter	16.4" to 17.6"
Maximum Friction Face	3.30"
Maximum Depth of Cut	0.015" / Side
Weight	7.68 lbs

PRECISION-MATCH CUTTING HEAD (Optional)

Maximum Rotor Thickness Minimum Rotor Thickness Maximum Rotor Diameter Maximum Friction Face Maximum Depth of Cut Weight

	2.00"
	0.20"
15.6" to	17.1"
	3.82"
0.020"	/ Side
9.	38 lbs

MACHINE
INIAGHINE

Spindle Speed	133 RPM
Carriage Speed	0.005" / rev.
Motor	1.00 HP
Shipping Weight	220 lbs.
Electrical Supply	120v / 1ph / 60hz
Feed Distance	6.95" (7.44"Opt.)

★ Pro-Cut's PFM lathes are the first choice of the brake service industry. We have been approved by virtually every auto manufacturer and are considered essential equipment by most OEM's. THIS SYSTEM IS SUBJECT TO ONE OR MORE OF U.S. PATENTS: 6,050,160 / 6,101,911 / 6,216,571 / 6,327,947 / 6,330,847 / 6,474,203 / 6,477,928 / 6,895,851 / 5,974,878 / 7,607,377

PRO-CUT International, LLC 10 Technology Drive #4 West Lebanon, NH 03784



NEVER OUTMATCHED"

